

TX70CL 4.0



HIKMICRO THUNDER TX70CL 4.0 features a high-sensitivity 1280×1024 thermal detector with a NETD of less than 12mK. Its 70mm F1.3 lens, powered by Image Pro 4.0, captures fine details at extended distances, while the zeroing-free design with 1 MOA adjustment accuracy enables precise point-of-impact adjustment. Its compact form makes it easy to handle and keeps the setup streamlined for the hunt.

● Key Feature

- 1280 x 1024 resolution @12μm thermal detector
- High sensitivity thermal module NETD < 12 mK (@25°C, F# = 1.0)
- 70mm, F1.3 lens with detection range up to 3500m
- 1920 × 1080 resolution 0.49-inch OLED display
- Built-in lens laser rangefinder up to 1200m
- HIKMICRO Shutterless Image System (HSIS)+Sync Pro
- Rechargeable and Replaceable Li-ion Battery, 5h continuous operation
- High shock resistance up to 6000J
- HIKMICRO Image Pro 4.0

• Specification

Thermal Module	
Image Sensor	Uncooled Focal Plane Arrays
Max. Resolution	1280x1024
Frame Rate	50Hz
Pixel Interval	12μm
Response Waveband	8μm to 14μm
Lens (Focal Length)	70mm, F1.3
NETD	Less than 12mK (25 °C, F#=1.0)
Focus Mode	Focus Knob
Detection Range	3500m
Min. Focusing Distance	10m
Magnification	1x
Field of View(H × V), Degrees / m @100m	12.8° ×10.3°/22.4 ×18 m
Recommended Magnification of the Day Scope	1-15x
magnification of monocular mode	2.4x-19.2x (8x)
Image Display	
Display	1920x1080, 0.49 inch, OLED
Palettes	Black Hot, White Hot, Red Hot, Fusion, Red monochrome, Green monochrome
Exit Pupil	25mm
Image Pro 4.0	Yes
Eye Relief	20mm
Brightness Adjustment	Yes
Tone Adjustment	Cold, Warm
HSIS (HIKMICRO Shutterless Image System)	Yes
Sync Pro	Yes
System	
Record Video	On-board Video Recording
Capture Snapshot	Yes
Virtual Reticle	Yes
Standby Mode	Yes
Storage	Built-in EMMC (64 GB)
Hotspot	Yes
Reticle	No
Audio Recording	Yes
Recoil-activation Recording	Yes
Max. Recoil	6000J
Local Album	Yes
Image Calibration	Yes
Zeroing Profiles	5


Power Supply	
Battery Type	HM-3840DC
Battery Operating Time	≥5h (25 °C, with hotspot off and LRF on)
Type-C Power Supply	5 VDC, 2 A Supports External Power Supply Supports Direct Charging
General	
Protection Level	IP67
Dimension	135mm × 64mm × 64mm
Weight	575g with Battery
Working Temperature	-30 °C to +45 °C (-22 °F to +113°F)
Body Material	Body & Lens Cover: Magnesium Alloy
Center Height	31mm
Laser Rangefinder	
Safety Class for Laser	Class 1
Wavelength	905nm
Max. Measuring Range	1200m
Measurement Accuracy	±1m < 400m ±0.3m > 400m
Min. Measuring Range	10m
LRF Module in Lens	Yes

▪ Available Model


HM-TRAC-70Y3G/WL-TX70CL 4.0

HM-TRAC-70Y3G/WL1-TX70CL 4.0


▪ Dimension




Battery Charger (x1)




USB Type-C Cable (x1)



Lint-free Cloth (x1)




Quick Start Guide (x1)



Batteries (x2)



Wrench (x1)



Carrying Case (x1)



Hikmicro Hunting.Global HIKMICRO Outdoor www.hikmicrotech.com [hikmicro_hunting_global](https://www.instagram.com/hikmicro_hunting_global) HIKMICRO info@hikmicrotech.com

Room 313, Unit B, Building 2, 399 Danfeng Road, Xixing Subdistrict, Binjiang District, Hangzhou, Zhejiang
© Hangzhou Microimage Software Co., Ltd. All rights reserved. | Data subject to change without notice!